
jira-agile-toolbox

Release unknown

Jef Neefs

Jun 05, 2021

CONTENTS

1 API documentation	3
2 Indices and tables	7
Index	9


```
pip install jira-agile-toolbox
```

CHAPTER
ONE

API DOCUMENTATION

class jira_agile_toolbox.JiraAgileToolBox(jira_client)
a class which helps you do agile things with jira

Parameters `jira_client (jira.JIRA)` – an instance of `jira.JIRA`

Example

```
>>> from jira import JIRA
>>> jira_client = JIRA("https://jira.atlassian.org")
>>> jat = JiraAgileToolBox(jira_client)
```

add_labels_to_all_sub_items_of_epic(epic, labels)
adds labels to all ‘Issues in Epic’

Parameters

- `epic (str jira.Issue)` – and epic key as a string or the epic as a `jira.Issue`
- `labels (str list)` – the label to set as a string or the labels to set as a list

Example

```
>>> from jira_agile_toolbox import JiraAgileToolBox
>>> from jira import JIRA
>>> my_jira_client = JIRA("https://my-jira-server.com", basic_auth=(  
    "MYUSERNAME", "MYPASSWORD"))
>>> tb = JiraAgileToolBox(my_jira_client)
>>> tb.add_labels_to_all_sub_items_of_epic("PROJ001-001", ["label_to_set  
    "])
```

this will append the “label_to_set” to all existing labels of all Issues in Epic

copy_fix_version_from_epic_to_all_items_in_epic(epic)
copies fixVersions from the epic to all ‘Issues in Epic’

Parameters `epic (str jira.Issue)` – and epic key as a string or the epic as a `jira.Issue`

Returns None

Example

```
>>> from jira_agile_toolbox import JiraAgileToolBox
>>> from jira import JIRA
>>> my_jira_client = JIRA("https://my-jira-server.com", basic_auth=(  
    "MYUSERNAME", "MYPASSWORD"))
>>> tb = JiraAgileToolBox(my_jira_client)
```

(continues on next page)

(continued from previous page)

```
>>> epic = my_jira_client.issue("PROJ001-001")
>>> epic.fields.fixVersions
[<JIRA Version: name='0.0.10', id='31063'>]
>>> tb.copy_fix_version_from_epic_to_all_items_in_epic(epic)
>>> tb.get_all_issues_in_epic("JAT-001")[:].fields.fixVersions
[<JIRA Version: name='0.0.10', id='31063'>]
```

get_all_issues_in_epic(epic, fields=None)

gets all 'Issues in Epic' as a list

Example

```
>>> from jira_agile_toolbox import JiraAgileToolBox
>>> from jira import JIRA
>>> my_jira_client = JIRA("https://my-jira-server.com", basic_auth=(
...     "MYUSERNAME", "MYPASSWORD"))
>>> tb = JiraAgileToolBox(my_jira_client)
>>> tb.get_all_issues_in_epic("JAT-001")
[<JIRA Issue: key='JAT-002', id='67'>, <JIRA Issue: key='JAT-003', id='68'
...>, <JIRA Issue: key='JAT-004', id='69'>]
```

Parameters

- **epic** (*str jira.Issue*) – and epic key as a string or the epic as a *jira.Issue*
- **fields** (*str list*) – a string or list of strings to limit the fields to get this helps to lower the amount of data to be sent around

Returns a list of *jira.Issues***Return type** list**get_storypoints_from_epic(epic)**

searches for the epic and returns the number of storypoints as a dict

Parameters **epic** (*str jira.Issue*) – and epic key as a string or the epic as a *jira.Issue***Returns** a dictionary containing total story points**Return type** dict

Example

```
>>> from jira_agile_toolbox import JiraAgileToolBox
>>> from jira import JIRA
>>> my_jira_client = JIRA("https://my-jira-server.com", basic_auth=(
...     "MYUSERNAME", "MYPASSWORD"))
>>> tb = JiraAgileToolBox(my_jira_client)
>>> tb.get_storypoints_from_epic("JAT-001")
{'total': 100, "Reported": 50, "Closed": 50}
```

rank_issues_at_top_of_project(ranked_list, project)

moves the provided ranked_list at the top of the backlog of the given project

Parameters

- **ranked_list** – a list of *jira.Issues*
- **project** (*str*) – project key

Example

```
>>> from jira_agile_toolbox import JiraAgileToolBox
>>> from jira import JIRA
>>> my_jira_client = JIRA("https://my-jira-server.com", basic_auth=(  
    "MYUSERNAME", "MYPASSWORD"))
>>> tb = JiraAgileToolBox(my_jira_client)
>>> tb.rank_issues_by_list([my_jira_client.issue("JAT-001"), my_jira_
    <client.issue("JAT-003")])
```

will produce following result

before	after
JAT-010	JAT-001
JAT-005	JAT-003
JAT-003	JAT-010
JAT-002	JAT-005
JAT-001	JAT-002

rank_issues_by_list(*ranked_list*, *on_top_of_issue*)

sorts the provided list by rank on top of the latter issue

Parameters

- **ranked_list** – list of issues to be sorted by rank index 0 has highest rank
- **on_top_of_issue** – issue on top of which these issues need to land

Example

```
>>> from jira_agile_toolbox import JiraAgileToolBox
>>> from jira import JIRA
>>> my_jira_client = JIRA("https://my-jira-server.com", basic_auth=(  
    "MYUSERNAME", "MYPASSWORD"))
>>> tb = JiraAgileToolBox(my_jira_client)
>>> tb.rank_issues_by_list([my_jira_client.issue("JAT-001"), my_jira_
    <client.issue("JAT-003")], my_jira_client.issue("JAT-005"))
```

will rank issues like:

before	after
JAT-010	JAT-010
JAT-005	JAT-001
JAT-003	JAT-003
JAT-002	JAT-005
JAT-001	JAT-002

**CHAPTER
TWO**

INDICES AND TABLES

- genindex
- modindex
- search

INDEX

A

`add_labels_to_all_sub_items_of_epic()`
(jira_agile_toolbox.JiraAgileToolBox method),
3

C

`copy_fix_version_from_epic_to_all_items_in_epic()`
(jira_agile_toolbox.JiraAgileToolBox method),
3

G

`get_all_issues_in_epic()`
(jira_agile_toolbox.JiraAgileToolBox method),
4
`get_storypoints_from_epic()`
(jira_agile_toolbox.JiraAgileToolBox method),
4

J

`JiraAgileToolBox` (*class in jira_agile_toolbox*), 3

R

`rank_issues_at_top_of_project()`
(jira_agile_toolbox.JiraAgileToolBox method),
4
`rank_issues_by_list()`
(jira_agile_toolbox.JiraAgileToolBox method),
5